

Technical Accessory Guides (TAGs)

For Associates, Resellers, ISVs and Alliance Partners

Global



Version: Active-Only

Will only show products that are known to be available for sale

Need to provide an update or change?

Contact <mailto:pgw786@zebra.com>



For Internal Use by
PartnerConnect Members Only



DS9308 Technical Accessory Guide



NOTE: This document is only for general reference. Solutions Pathway and related PMBs should be used for product availability, pricing, and final solution selection.





* Zebra does not endorse or specifically recommend any **third-party products, accessories, or hardware**. ZEBRA DISCLAIMS ANY AND ALL LIABILITY, INCLUDING ANY EXPRESS OR IMPLIED WARRANTIES, WHETHER ORAL OR WRITTEN, FOR SUCH THIRD PARTY PRODUCTS, ACCESSORIES, OR HARDWARE. THE CUSTOMER ACKNOWLEDGES THAT NO REPRESENTATION HAS BEEN MADE BY ZEBRA AS TO THE FITNESS OF THE THIRD-PARTY PRODUCTS, ACCESSORIES, OR HARDWARE FOR THE CUSTOMER'S INTENDED PURPOSE.












Communication Cables








Standard USB Cables





Part Number	Picture	Description	Notes	Required Items
CBA-U21-S07ZBR		USB Cable: Series A Connector, 7ft. Straight		
CBA-U30-S15ZBR		USB Cable: Series A Connector, 15ft. Straight	► has heavier gauge wire vs. CBA-U30-S15ZAR, can support 5V and 12V power, scanner dependent	
CBA-U32-C09ZAR		USB Cable: (Series A Connector, 9ft. Coiled)		
CBA-U29-C15ZBR		USB Cable: Series A Connector, 15ft. Coiled	► has heavier gauge wire vs. CBA-U29-C15ZAR, can support 5V and 12V power, scanner dependent	
CBA-U26-S09EAR		USB Cable:EAS, Series A Connector, 9ft. Straight	Integrates with Checkpoint EAS security tag system	
CBA-U65-S07ZAR		USB Cable: USB-C Connector, 7ft. Straight	► Cable is typically used with tablets and laptops with USB-C ports	

IBM POS USB Cables



Part Number	Picture	Description	Notes	Required Items
CBA-U23-S07ZBR		USB Cable: Power Plus Connector, 7ft. Straight, 12V	► has heavier gauge wire vs. CBA-U23-S07ZAR, can support 5V or 12V power, scanner dependent	
CBA-U35-S15ZBR		USB Cable: Power Plus Connector, 15ft. Straight	► Has heavier gauge wire vs. CBA-U35-S15ZAR, can support 5V or 12V power, scanner dependent	
CBA-U34-C09ZAR		USB Cable: Power Plus Connector, 9ft. Coiled		
CBA-U28-C15ZBR		USB Cable: Power Plus Connector, 15ft. Coiled	► Has heavier gauge wire vs. CBA-U28-C15ZAR, can support 5V and 12V power, scanner dependent.	



CBA-U27-S09EAR		USB Cable: Power Plus Connector, 9ft. Straight with EAS	Integrates with Checkpoint EAS security tag system	
RS232 Cables				
Part Number	Picture	Description	Notes	Required Items
CBA-R01-S07PBR		RS232 Cable:STD-DB9 Female, TxD on 2, 7ft. Straight	► Includes improved TTL current limit protection circuitry vs. CBA-R01-S07PAR	Requires external power supply
CBA-R02-C09PAR		RS232 Cable:STD-DB9 Female, TxD on 2, 9ft. Coiled		Requires external power supply
CBA-R03-C12PAR		RS232 Cable:STD-DB9 Female, TxD on 2, 12ft. Coiled		Requires external power supply
CBA-R06-C20PBR		RS232 Cable:STD-DB9 Female, TxD on 2, 20ft. Coiled	► Includes improved TTL current limit protection circuitry vs. CBA-R06-C20PAR	Requires external power supply
CBA-R46-C09ZBR		RS232 Cable: True Cvtr, DB9 Female, Pwr Pin 9, TxD on 2, 9ft. Coiled	► Cable provides ±5V signaling (RS232C) needed by some older PLC's which may not support TTL signalling	
CBA-R37-C09ZBR		RS232 Cable: STD-DB9 Female, PWR Pin 9, 9ft coiled	► Includes improved TTL current limit protection vs. CBA-R37-C09ZAR.	
CBA-R73-C09ZAR		RS232 Cable: True Cvtr, DB9 Male, Pwr Pin 9, TxD on 2, 9ft. Coiled	► Cable provides ±5V signaling (RS232C) needed by some older PLC's which may not support TTL signalling	
CBA-R32-S07PAR		RS232 Cable: True Cvtr, DB9 Female, TxD on 2, 7ft. Straight	► Cable provides ±5V signaling (RS232C) needed by some older PLC's which may not support TTL signalling	Requires external power supply
Siemens Nixdorf Beetle POS Terminal RS232 Cables				
Part Number	Picture	Description	Notes	Required Items
CBA-R08-S07ZBR		RS232 Cable: Nixdorf Beetle-5V Direct Power Cable 7ft. Straight	► Includes improved TTL current limit protection circuitry vs. CBA-R08-S07ZAR	
CBA-R09-C09ZAR		RS232 Cable: Nixdorf Beetle-5V Direct Power Cable 9ft. Coiled		
CBA-R10-S07ZBR		RS232 Cable: Nixdorf Beetle-12V Direct Power, 7ft. Straight	► Includes improved TTL current limit protection circuitry vs. CBA-R10-S07ZAR	
CBA-R13-S09EAR		RS232 Cable: Nixdorf Beetle-12V Direct Power, 7ft. Straight., with EAS	Integrates with Checkpoint EAS security tag system	

Other POS Terminal RS232 Cables				
Part Number	Picture	Description	Notes	Required Items
CBA-R24-C20ZAR		RS232 Cable: Fujitsu Team POS 500 ICL, 20ft Coiled		
CBA-R31-C09ZAR		CBL:RS232 (NCR7448) 9FT,CLD		
CBA-R47-C09ZAR		CBL:RS232 (NCR AUX PORT) 9FT, CLD		
25-32465-26		RS232 Cable: Datalogic Magellan scanner Auxiliary Port, 6ft Coiled	► RJ50 cable connects to Datalogic Magellan Slot Scanner Auxiliary Port	
CBA-R28-C09ZAR		RS232 Cable: Verifone Ruby, 9ft, Coiled		
IBM 468x/469x POS Cables				
Part Number	Picture	Description	Notes	Required Items
CBA-M61-S07ZAR		IBM 468x/9x, Port 9B Cable, 7ft. Straight	► Port 5B connection provides 5V power and will charge scanner in about 4 hours. ► Supports host auto-detect so configuration barcode is not needed to put device into IBM Host mode.	
Scanner Emulation Cables (Not supported by DS9308)				
Wand Cables (Not supported by DS9308)				
Synapse Adapter Cables (Not supported by DS9308)				
Terminal Specific Cables				
CBA-A51-S16ZAR		Auxiliary Scanner Cable to MP6000/MP7000, RS232 Serial	► Allows handheld scanners to be used with MP6000/MP7000 for scanning heavy/awkward items. ► 5 meter length ► RS232 serial connection to scanner ► Connects to AUX2 port on MP6000/MP7000 ► Provides power to corded scanners ► NOTE: MP6000/MP7000 supports maximum of 2 auxiliary scanners.	
Misc				
Part Number	Picture	Description	Notes	Required Items

BRKT-MM0093C-04		Desk/Multi-Mount Bracket (Black color)		
BRKT-MM0093C-0W		Desk/Multi-Mount Bracket (White color)		
BRKT-LM0093C-04		Locking Mount Bracket (Black color)		
BRKT-LM0093C-0W		Locking Mount Bracket (White color)		

Power Supplies/Power Cords

Part Number	Picture	Description	Notes	Required Items
PWR-WUA5V4W0US		Power Supply (US)	<ul style="list-style-type: none"> ► Used when connecting communication cables labeled above as "Requires external power supply". ► For use in US, CA, MX, JP, TW. ► 5.2V, 1.1A, 5.7W ► Provides US DOE Level VI compliance for power efficiency. ► Replaces PWRS-14000-253R 	
PWR-WUA5V4W0IN		Power Supply (India)	<ul style="list-style-type: none"> ► Used when connecting communication cables labeled above as "Requires external power supply". ► For use in India. ► 5.2V, 1.1A, 5.7W ► Provides US DOE Level VI compliance for power efficiency. ► Replaces PWRS-14000-254R 	

PWR-WUA5V4W04C		Power Supply (EU, UK, Brazil, Australia, China)	<ul style="list-style-type: none"> ► Used when connecting communication cables labeled above as "Requires external power supply". ► Includes AC adapter clips for use in EU, UK, Brazil, Australia and China. ► 5.2V, 1.1A, 5.7W ► Provides US DOE Level VI compliance for power efficiency. 	
23844-00-00R		AC Line Cord	<ul style="list-style-type: none"> ► This AC Line Cord is for use in North America. See the AC Line Cords by Country TAG for comparable line cords to use in other countries. 	